



Specification:

- 1). Driving: Duty:1/32, Bias:1/6, VLCD:4.8V, VDD:5.0V
- 2). Viewing angle: 6 0'clock
- 3). Display mode: STN/Positive/Transflective/Y-G
- 4). Operating temp.: -20°C~+70°C
Storage temp.: -30°C~+80°C
- 5). IC: SDN1661
- 6). Backlight: Side Yellow-green
- 7). Dimensions with mark "*" are important, with mark "()" are referenced
- 8). All the raw materials are RoHS compliant

PIN	1	2	3	4	5	6	7	8	9
CONNECTION	VDD	VSS	V0	RES	E1	E2	R/W	A0	DB0
PIN	10	11	12	13	14	15	16	17	18
CONNECTION	DB1	DB2	DB3	DB4	DB5	DB6	DB7	BLA	BLK

REV	REVISION RECORD	DATE	MODEL NO.		GENERAL TOL: ±0.3	
A0	First issue	3-12	SYB12232F		未注公差	
			APPROVED BY	CHECKED BY	DRAWING BY	PAGE: 1 OF 1
						UNIT: mm
						PROJECTION
						三角法


深圳市三元晶液晶显示科技有限公司
 Shenzhen TCC LCD Hi-Tech Co., Ltd.