





DOTS SIZE  
SCALE 20:1



PIN	1	2	3	4	5	6	7	8	9	10	11
CONNECTION	VSS	VDD	V0	C/D	/WR	/RD	/RST	DB0	DB1	DB2	DB3
PIN	12	13	14	15	16	17	18	19	20	21	22
CONNECTION	DB4	DB5	DB6	DB7	CS1	CS2	CS3	CS4	VOUT	BLK	BLK

Specification:

- 1). Driving: Duty: 1/128, Bias:1/9, VLCD:1.3.0V(Ref), VDD:5.0V
- 2). Viewing angle: 6 0'clock
- 3). Display mode: STN/Positive/Transflective/YG
- 4). Operating temp.: -20°C~+70°C  
Storage temp.: -30°C~+80°C
- 5). IC: AP31107/31108(or compatible)
- 6). Backlight: Edge YG
- 7). Dimensions with mark "\*" are important, with mark "()" are referenced
- 8). All the raw materials are RoHS compliant

REV	REVISION RECORD	DATE					深圳市三元晶科技有限公司 ShenZhen TCC LCD Hi-Tech Co., Ltd.		GENERAL TOL: ±0.3 未注公差	
A0	First issue	12-9	MODEL NO.	SYB128128DV10-5C9YL3NIR-B5WG	CHECKED BY	DRAWING BY	PAGE: 1 OF 1	UNIT: mm	PROJECTION	 三角法
			模 组 型 号				面	单 位		
			APPROVED BY							